

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/056684 A2

(51) International Patent Classification⁷:

B65H 5/06

(21) International Application Number:

PCT/EP2003/014783

(74) Agents: BURKE, Steven, D. et al.; R.G.C. Jenkins & Co.,
26 Caxton Street, London SW1H 0RJ (GB).

(22) International Filing Date:

19 December 2003 (19.12.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02258869.3 23 December 2002 (23.12.2002) EP

(84) Designated States (*regional*): ARIPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,
SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): MARS,
INCORPORATED [US/US]; 6885 Elm Street,, McLean,
VA 22101-3883 (US).

Published:

- without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2004/056684 A2

(54) Title: BANKNOTE CONVEYOR

(57) **Abstract:** A banknote conveyor which includes moveable means for transporting a banknote, the means engaging frictionally with the banknote at at least three points so that the force driving the banknote is dependent on the rigidity of the note. The banknote can further swivel about one of the points to align the note with a desired path. Also provided is a means for limiting the movement of the banknote if the force required to convey the banknote exceeds a predetermined limit and means for preventing the insertion of banknotes or other foreign objects into the conveyor when not in use.